

HYBRID FIBER RESIN SERIES


FIXED WINDOWS

The Hybrid Fiber Resin Fixed Window delivers high-performance design with sweeping views, combining glass-fiber reinforced PVC profiles and Low-E Foil insert technology for superior thermal efficiency. Built for strength, stability, and sustainability, it accommodates triple glazing, enhances acoustical performance, and provides exceptional durability for both commercial and residential applications.





PHIUS CERTIFIED



FRFIXED

PRODUCT DATA


	PERFORMANCE
Certification	CW/AW 100
Test Size	48"x72"
U-Value	0.14
Air Infiltration Rate @ 6.24 psf	<0.1 cfm/sf
Water Test Pressure	12 psf
Design Pressure	100 psf
Frame Depth	3 ¹ / ₈ "
Thermal Break Design	Polyamide Strut
Standard Glass Thickness	1"
Glazing Material	Dry Glazed
OITC/STC	Up to 33 / Up to 40

*Glass package may effect data.

FEATURES AND BENEFITS

- Glass fiber reinforced PVC frame for superior strength
- Advanced Low-E foil insert option for maximum performance
- Co-extruded compression seals for airtight performance and thermal efficiency
- Seven chambers in the frame
- Accommodates triple glazing
- Improved acoustical performance
- Passive House certified

TYPICAL CONFIGURATIONS



*Please consult your project engineer for additional configuration options.



**VISIT OUR
WEBSITE**



SEE EVERYTHING WE HAVE TO OFFER!
VISIT [PEERLESSPRODUCTS.COM](https://www.peerlessproducts.com)